

# 2024

## Metal Detector 3 zone

[www.hlogicgroup.com](http://www.hlogicgroup.com)



## HST270SA - 3 Series

### Side Panel Digital Control Box



WATERPROOF



ACCESS CONTROL  
CONNECTING



LED LIGHT  
INDICATOR



MODULAR  
DESIGN



PASSWORD  
PROTECTION



VOLUME  
ADJUSTABLE



HIGH  
PRECISION



LED DISPLAY





SENSITIVITY  
ADJUSTABLE

- Space saving size to fit all entrance ;
- Reliable 3 detection zones with fast detecting speed;
- Quick and simple setup for immediate use;
- User -friendly operation;
- 3 Years warranty;

Conform to Electricity EN60950 Safety Standard


Conform to Radiation EN50081 - 1 Standard

Conform to Anti - interference EN50082 - 1 Standard



## Product Specification

Overall Exterior Size	2165*828*349mm
Passageway Interior Size	2017*720*349mm
Operating Voltage	AC100V ~240V 50 / 60Hz
Power	12W
Operating Temperatures	-20 ~ 65
Installation Environment	Width 100cm* Length 200cm (minimum range without metal)




## Function Configuration

Detection Zones	3 Vertical Zones
Pass Count	0-99999
Alarm Count	0-99999
Metal Detection Accuracy Range	One - dollar coin
User Interface	Dual sets of bright red and green digital tube display + integrated four - button panel operation mode
Password Protection Function	5 - digit password protection
Operating Frequency	0-99
Security Level	0-99
Sensitivity Level	0-400
Alarm Volume	0-99
Alarm Tone	1-99
Alarm Time	1-99
Scene Setting	72 preset scenes
Infrared Setting	0-Both groups OFF 1-Front group ON 2-Rear group ON 3-Both groups ON
Left and right LED Bars	Interchangeable
LED Alarm Bars	Front 2 groups
Simultaneous detection and alarm in multiple zones	2 Detection zones simultaneously alarm


## Optional Functions: The above zones can be equipped with the following functions

- Secondary Development Port/Upgrade Port
- Front and Rear Panel Alarm LED Lights
- Turnstile Connection

## Interface Display




## Anti - interference Reference Standard



Keep  $\geq 80\text{cm}$  from the X - Ray machine




Keep  $\geq 50\text{cm}$  between two units




Keep  $\geq 10\text{cm}$  from the wall

**Note:** The above distances are for reference only, and the actual distances shall be subject to the performance accuracy of on -site debugging; the higher the sensitivity, the greater the distance interval, and the lower the sensitivity, the smaller the distance interval.

## Test kits



## Detection Zone



## Package

Packaging :	Carton box
Package Size :	L2245xW635 xH200mm
Volume :	0.29m <sup>3</sup>
Net weight :	24kg
Gross weight :	30kg





MORE THAN SECURITY



[www.hlogicgroup.com](http://www.hlogicgroup.com) 🔍